

553, 820

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012432 A1

(51) International Patent Classification⁷: **C08L 83/14**

(21) International Application Number:
PCT/US2004/023266

(22) International Filing Date: 19 July 2004 (19.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/490,172 25 July 2003 (25.07.2003) US

(71) Applicants (for all designated States except US): **DOW CORNING CORPORATION** [US/US]; 2200 West Salzburg Road, Midland, MI 48686-0994 (US). **DOW CORNING TORAY SILICONE CO., LTD.** [JP/JP]; 4th floor AIG Building, 1-1-3, Marunouchi, Chiyoda-ku, Tokyo 100-0005 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **AKITOMO, Hiroshi** [JP/JP]; Minami 2-16-13, Chiharadai, Ichihara-Shi, Chiba prefecture (JP). **COLE, Richard, LeRoy** [US/US]; 311 Grove Circle, Avon Park, FL 33825 (US). **LUTZ, Michael, Andrew** [US/US]; 408 East Saiko Road, Hope, MI 48628 (US). **SWANSON, Stephen, Paul** [US/US]; 914 Wildrose Drive, Brea, CA 92821 (US). **YANG, Hyung-II** [KR/KR]; 690-1 KwangHyeWon-Ri, KawagHyeWon-Myon, Jincheon-Gun, ChoongBuk 365-830 (KR).

(74) Common Representative: **DECESARE, James, L.**; IP Department - Mail CO1232, Dow Corning Corporation, 2200 West Salzburg Road, Midland, MI 48686-0994 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations

— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only


Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: **SILICONE RUBBER COMPOSITION**



(57) Abstract: A silicone rubber composition exhibiting superior adhesive properties with respect to organic resins it comes into contact with during its cure, while at the same time possessing superior mold release properties with respect to metal dies used for its molding, contains: (A) a polyorganosiloxane having at least two silicon-bonded alkenyl groups per molecule; (B) a polyorganosiloxane having at least two silicon-bonded hydrogen atoms per molecule; (C) an alkylene glycol ester of diacrylic acid or an alkylene glycol ester of dimethacrylic acid having the formula (I), wherein R¹ is hydrogen or a methyl group, R² represents an alkylene group, and n has a value of 1-10; and (D) a platinum catalyst.

WO 2005/012432 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.